Original Research

Removal of Sulfa Antibiotics in Low-Temperature Water Using Scoria

Rui Li^{1, 2}, Yuling Zhang^{1, 2*}, Jiali Wang^{1, 2}, Hong Qian^{1, 2}

¹Key Laboratory of Groundwater Resources and Environment, Ministry of Education, Jilin University, Changchun 130021, China

²Institute of Water Resources and Environment, Jilin University, Changchun 130021, China

Received: 21 October 2016 Accepted: 29 December 2016

Abstract

Scoria, a natural silicate mineral, was used for the adsorption removal of antibiotics from water. The kinetics of adsorption were studied during the experiment and the results showed that the adsorption of three antibiotics (sulfathiazole (ST), sulfamethazine (SM2), and sulfamethoxazole (SMX)) by scoria fit the Freundlich isotherm well. Additionally, batch experiment data were fitted using pseudo first-order and pseudo second-order equations, and the calculated capacities for the three antibiotics were 0.7688, 0.7242, and 0.6341mg/g, respectively. Moreover, the effects of various water chemistry factors on the removal of the three antibiotics were explored, and Fe²⁺ and Mg²⁺ were found to promote the adsorption. The alkalinity and hardness of water both had significant effects on absorption of the three antibiotics by scoria. The carbon content of scoria increased significantly, and energy dispersion spectrum analysis showed that it could remove three sulfa antibiotics from low-temperature (10°C) water effectively. Overall, scoria is an effective natural material for purifying low-temperature water polluted with ST, SM2, and SMX.

Keywords: scoria, removal, antibiotics, effects

Introduction

Organic contaminants can infiltrate aquifers via various channels. In recent years, antibiotics have been widely applied for treatment of disease in humans and to prevent infections and promote growth in livestock [1-2]. Veterinary drugs, especially antibiotics, have recently gained a great deal of attention as emerging contaminants. Indeed, antibiotics have been detected in groundwater, landfill leachate, and surface water worldwide [3-5]. Moreover, sulfamethazine (SM2), sulfamethoxazole (SMX), and tetracycline have been found in groundwater in Iowa in the United States [6], while 60 types of drugs, including sulfamethoxazole (SMX), were detected in underground well water samples of Baden-Wuerttemberg in Germany [7]. Sulfamethoxazole and sulfamethazine were also detected in groundwater in Wisconsin in the United States. The frequency of detection of SMX and SM2 were 70% and 10%, respectively [4]. At least eight kinds of drugs can be simultaneously detected when analyzing any three samples, and the detection rate can reach 20%. Four kinds of sulfa antibiotics have also been detected at sites offshore of Xiamen at levels of 2-9 ng/L [8]. The abuse of antibiotics not only harms the environment, but also has the potential to damage human health [9-10].

^{*}e-mail: lr4636@163.com

Sulfathiazole (ST), sulfamethazine (SM2), and sulfamethoxazole (SMX) have commonly been used as additives for sulfa antibiotics of which trace levels have been detected [11-17]. Four types of sulfa antibiotics were found in samples of soil and groundwater in a farm in northeastern China [18]. Domestic sewage and aquaculture wastewater containing antibiotics can threaten the safety of residents' drinking water. Despite the threat of trace amounts of antibiotics, there are no drinking water standards for antibiotics in China at present. Nevertheless, identifying methods of removing sulfa antibiotics from water has received a great deal of attention [19-22]. Removal of antibiotics from drinking water [23] using nanofiltration has been investigated; however, experiments showed that the small molecules required nanofilters of smaller aperture [24]. As a result, this process is easily hindered by membrane fouling and decreasing membrane flux, resulting in the need for much more energy. Activated carbon is a common adsorbent for pollutant removal, and experiments have shown that activated carbon powder has good effects on the removal of trace antibiotics [25], with smaller activated carbon particles and longer treatment times producing better results, but at a higher cost.

Scoria is a natural silicate of lightweight aggregate formed during volcanic eruptions. Because of its porosity, low density, and adsorption capacity, scoria has been widely studied for its potential use in building materials such as lightweight concrete [26]. Scoria has also been used as a material for removing fluoride from groundwater by adsorption [27-28]. However, few studies have investigated the removal of contaminants by scoria. In light of its porosity, low weight, uniform particles, and good adsorption performance, scoria has a unique advantage for the removal of contaminants. Therefore, this study investigated the use of scoria for removal of sulfa antibiotics from water to determine its potential for large-scale contaminant removal.

Materials and methods

Main Materials

Scoria with a particle size of 0.85-2 mm (after treatment) was obtained from a volcanic field in northeast Jilin Province, China. Three antibiotics (ST, SM2, and SMX) were purchased from Sigma (St. Louis, MO, USA). All chemical reagents were of analytical grade and purchased from Beijing Chemical Co. (Beijing, China). The solutions of three antibiotics were prepared by diluting antibiotic solutions with deionized water.

Experimental Methods

To investigate the influence of water chemistry factors on antibiotic adsorption, 0.50 g of scoria were added into antibiotic solution at 5.00 mg/L in a 60.00 mL polyethylene bottle. The water environment in bottles was confirmed with the following requirements (Table 1) and

Table 1. Ion concentrations in each group after mixing (mg/L).

	Ion Concentration						
Group	Mn ²⁺	Fe ²⁺	CO ₃ ²⁻	Ca ²⁺	Mg ²⁺		
C1	0	0	0	0	0		
C2	0.50	0.50	5.00	50.00	50.00		
C3	1.00	5.00	10.00	100.00	100.00		
C4	2.00	10.00	30.00	200.00	200.00		
C5	4.00	30.00	50.00	300.00	300.00		
C6	8.00	50.00	100.00	500.00	500.00		

a control group was set, then the bottles were shaken at 120 rpm in an incubator shaker for 4 hours and kept at 10°C. The concentration of antibiotics in the supernatant was analyzed by high-performance liquid chromatography (HPLC-UC) using an Agilent Intelligent UV detector (270 nm), the chemical compositions of scoria were analyzed by an energy dispersion x-ray detector (EDX) (JSM-6700F on Windows NT, 2010), and the scoria's carbon (C) content was analyzed through the EDX spectrum before and after adsorption.

Batch Equilibrium and Kinetic Adsorption

A batch experiment was conducted to determine the reaction time required to reach adsorption equilibrium. Briefly, scoria (0.50 g) was added to a series of 60 polyethylene bottles with 40 mL diluted solutions (0.5-10 mg/L), after which the bottles were shaken at 120 rpm and kept at 8°C for various lengths of time in an incubator shaker. The quantity of adsorbed antibiotics was then calculated based on the difference between the initial and residual amounts of antibiotics in solution. The antibiotics adsorption at equilibrium was calculated using the following equation:

$$q_e = \frac{\left(C_0 - C_e\right)V}{M}$$

...where q_e is the equilibrium concentration, C_0 and C_e are the initial concentration and equilibrium concentrations of antibiotics, respectively, M is the mass of scoria, and V is the volume of the solution. The initial concentrations were set at 0.5, 1, 2, 5, 8, and 10 mg/L. The samples were filtered through a 0.22 µm cellulose membrane and the concentration of antibiotics were analyzed by HPLC-UV. All batch experiments were conducted at 8°C and all experiments were repeated three times.

Test Methods

Water samples were filtered through cellulose membranes (0.22 μ m) before detection, after which the concentrations of ST, SM2, and SMX were measured by HPLC. Analyses were conducted using an XDB C18

column (4.6 mm×150 mm×5 μ m), a column temperature of 25°C, and a UV detector wavelength of 270 nm. The mobile phase consisted of methanol and 0.1% formic acid at a 3:7 ratio. The injection volume was 20 μ L and the flow rate was 1 mL/min.

The microstructure physical composition and mineral composition of scoria were analyzed by scanning electron microscopy.

Results and Analysis

Adsorption Kinetics

The experimental kinetics data used to examine the mechanism controlling adsorption processes were fitted using pseudo first-order and pseudo second-order equations as follows:

(a) pseudo first-order
$$\log (q_e - q_t) = \log q_e - \left(\frac{k_1}{2.303}\right) t$$

(b) pseudo second-order $\frac{t}{q_t} = \frac{1}{k_2 q_e^2} + \frac{t}{q_e}$

...where q_e and q_t were the adsorption capacity of antibiotics at equilibrium and at time t (min), respectively, and k_1 and k_2 were the rate constant of pseudo first- and second-order adsorption, respectively.

The quasi second-order kinetic model was based on the assumption that the adsorption rate was determined by the square of the unoccupied adsorption vacancies on the adsorbent's surface, and the linear relationship between t and t/q_t indicated that the adsorption had secondary adsorption kinetics characteristics.

Linear plots of pseudo first- kinetics and second-order kinetics are shown in Figs 1 and 2. According to the fitted curves in Fig 2. 1 and 2, the parameters were shown in Table 2. As shown in the table, the adsorption data were well represented by the pseudo second-order model as indicated by regression correlation coefficients of $R^{2}>0.99$ for the three antibiotics. These findings demonstrated that the experimental results were better described by the quasi second-order kinetic model than the pseudo first-order model, so the rate-limiting step would be the adsorption mechanism. The calculated q_e values of the three antibiotics were 0.7688, 0.7242, and 0.6341 mg/g, respectively.



Fig. 1. Linear plot of pseudo-first-order kinetics.



Fig. 2. Linear plot of pseudo-second-order kinetics.

Adsorption Isotherms

Equilibrium adsorption isotherms such as Langmuir and Freundlich isotherms were not only important methods to reflect the adsorption characteristics, but also the adsorption theory of the practical application system, which was developed according to the assumption that every adsorption was equivalent and the ability of a particle to bind there was independent of whether or not adjacent positions were occupied.

(c) Langmuir equation:

$$\frac{1}{q_e} = \frac{1}{q_m} + \frac{1}{K_L q_m} * \frac{1}{C_e}$$

(d)Freundlich equation:

$$\log q_e = \log K_f + \frac{1}{n} \log C_e$$

Table 2. Kinetic parameters for the removal of three antibiotics by scoria.

Adaarbata		Pseudo first-order		Pseudo second-order			
Ausoibate	q _e (mg/g)	K ₁	R ²	q _e (mg/g)	K ₂	R ²	
ST	0.5825	0.0309	0.995	0.7688	0.0654	0.9981	
SM2	0.4532	0.0299	0.982	0.7242	0.037	0.998	
SMX	0.7295	0.0230	0.9886	0.6341	0.0506	0.9988	

coefficients. Langmuir and Freundlich equations were plotted for the three antibiotics, and the respective parameters are shown in Table 3. The R^2 values of all of the regression correlation coefficients were >0.93, which suggested that Freundlich models were more suitable for describing the adsorption behavior of three antibiotics. Therefore, the Langmuir equation was not suitable for describing the adsorption behavior of the three antibiotics because this model assumes that the adsorption and desorption rates are identical. Freundlich's equation was more suitable for adsorption by scoria, and the regression correlation coefficients of the three antibiotics were 0.9441, 0.9465, and 0.9378, respectively.

Influence of Water Chemistry Factors on Antibiotics Adsorption by Scoria

Influences of Fe and Mn

Iron and manganese are trace elements essential for human health. Iron is the most abundant transition metal in several tissues and is involved in many processes, including DNA and protein synthesis. Although Fe deficiency will lead to a variety of motor disorders [29-31], long-term consumption of water enriched with Fe or Mn has adverse effects on health. The main form of Fe in natural groundwater is Fe²⁺, which is easily oxidized to Fe³⁺, resulting in turbid groundwater. In groundwater, Fe and Mn coexisted, with Mn showing valence values from +2 to +7. These findings are not surprising because these are the most common valence states and all other states except +2 and +4 are very unstable in groundwater under neutral conditions. Manganese is commonly found in the form of suspended particulates or solid matter in groundwater and in the form of Mn²⁺ and +4 in natural groundwater. The content of iron is generally 5-10 mg/L and the content of manganese is approximately 0.5-2.0 mg/L in groundwater throughout most of China. This study explored the effects of Fe²⁺ and Mn²⁺ on the adsorption of three antibiotics by scoria (Figs 3 and 4).

Both Fe²⁺ and Mn²⁺ played a positive role in the absorbance of the three antibiotics by scoria. Adsorption effects of antibiotics by different ions at different concentrations differed. Overall, the increase in adsor-



Fig. 3. Effect of Fe2+.



Fig. 4. Effect of Mn2+.

bance capacity of the three antibiotics promoted by Fe²⁺ was greater than that promoted by Mn²⁺. Under the condition of high iron and manganese content, Fe²⁺ can be partially oxidized to Fe³⁺ during the adsorption process. This leads to hydrolysis and production of Fe(OH),, which has a high adsorption ability; therefore, removal efficiency increased. However, the removal efficiency of the three antibiotics in the Mn²⁺ solution was lower than that in the Fe²⁺ solution. There were different reasons for these results. On one hand, it was not easy for Mn²⁺ to hydrolyze and produce colloid substances when the concentration of Mn²⁺ solution was low. On the other hand, the functional groups of antibiotics (-NH₂) were generated by hydrolysis and the hydrolysis product OH⁻ reacted with Mn²⁺ to form $Mn(OH)_{2}$, which caused the amount of Mn^{2+} to decrease. Overall, the results showed that scoria has a good effect on adsorption removal of ST, SM2, and SMX from groundwater.

Table 3. Langmuir and Freundlich parameters for adsorption of the three antibiotics.

Adaarbata	Langmuir model			Freundlich model			
Ausorbate	$q_m (mg/g)$	b (L mg ⁻¹)	R ²	K _f	n	R ²	
ST	0.6954	5.6840	0.7751	0.1370	2.2889	0.9441	
SM2	0.5312	5.5050	0.8164	0.1173	2.2148	0.9465	
SMX	0.4445	6.3855	0.8057	0.0969	2.2124	0.9378	



Fig. 5. Effect of Ca2+.



Fig. 6. Effect of Mg2+.

Effect of Hardness

Hardness of water, which is mainly determined by the content of cations such as calcium and magnesium [32], is an important water quality monitoring index. According to the hygienic standard for drinking water (GB5749-2006), the limit for hardness of drinking water is 450 mg/L (based on CaCO₃). Moreover, the hardness of water has significant effects on industries such as leather making [33]. In the present study, the influence of water hardness on the adsorption of three antibiotics by scoria was investigated. All samples showed concentrations of Ca²⁺ and Mg²⁺ below 500 mg/L (Figs 5 and 6).

As shown in Fig. 5, Ca^{2+} had a negative effect on SM2 and SMX absorbance, but a positive effect on ST absorbance, which improved by 50%. Additionally, Mg^{2+} promoted the absorption of all three antibiotics, with that of SMX doubling. Overall, both Mg^{2+} and Ca^{2+} had positive effects on adsorption of ST. Additionally, the effects of water hardness on adsorption were much weaker than those of Fe²⁺ and Mn²⁺, primarily because Ca²⁺ and Mg²⁺ were harder to hydrolyze, which led to the formation of lower amounts of hydrolysis products and therefore reduced antibiotics adsorption.

Influences of Alkalinity

Alkalinity is a measure of the capacity of water to neutralize acids, which is important to drinking and



Fig. 7. Effect of alkalinity.

irrigation water. One of the most common ions present in groundwater is CO_3^{2-} , which is a major factor of alkalinity in groundwater and plays an important role in the regulation of pH balance and maintenance of homeostasis in humans. Accordingly, it is necessary to test for CO_3^{2-} in domestic water and drinking water. Because it is easily hydrolyzed under certain conditions, solutions become alkaline when they contain CO_3^{2-} . In the present study, we explored the effects of CO_3^{2-} on adsorption of the three antibiotics by scoria (Fig. 5).

As shown in Fig. 5, CO_3^{2-} inhibited the adsorption of the investigated antibiotics by scoria. Specifically, the adsorption of ST, SM2, and SMX decreased by 16%, 6%, and 4%, respectively. The negative effects occurred because amino (-NH₂) groups reacted with hydrogen ions of water, forming weakly covalently charged ions that led to an overall increase in the concentration of hydroxyl ions, causing the solution to become alkaline. However, the presence of OH⁻ in water inhibited the hydrolysis of amino groups (-NH₂) because they can react with H₂O and produce OH⁻. CO_3^{2-} can continuously hydrolyze with water, causing the solution to become alkaline. This change in alkalinity decreases antibiotics solubility and therefore their removal rates decreased.

Physical and Chemical Indicators and Characterization of Microstructure of Scoria

Scoria is a low-density and porous material formed by magma passing through volcanic channels and cooling. The pores in scoria form after gas escapes during the cooling process, resulting in its porous, lightweight, particle uniformity, high permeability, and good hydraulic

Table 4. Main compounds of scoria.

Compounds	Contents	Compounds	Contents
SiO ₂	48-50%	CaO MgO	10-15%
Al ₂ O ₃ 15-20%		others	<5%
Fe ₂ O ₃	10-15%		

Indexes	Quantity	Indexes	Quantity
Density	500-600 Kg/m ³	Surface area	8×10^{3} -1.5 $\times 10^{4}$ cm ² /g
Share	2.4-2.6	Intercepted impurities	10-13 Kg/m ³
Compressive strength	7.00-8.25 Kg/cm ²	Nonuniformity coefficient	1.4-1.6
Porosity	74-78%	Head loss	<12 cm/m

Table 5. Physical and chemical properties of scoria.

conductivity. These characteristics impart scoria with unique advantages for dealing with contaminated groundwater. Scoria has been investigated for its potential for use in building materials; however, few investigations of its use in water treatment have been conducted. The main components of scoria are quartz, alkali-feldspar, plagioclase, and clay, and these components are the primary factors influencing its activity. Different components of scoria have different effects on its adsorption capacity. As shown in Tables 4 and 5, the major oxides of scoria are SiO₂, Al₂O₃, Fe₂O₃, CaO, and MgO.



Fig. 8. SEM micrograph before adsorption.

Analysis of Microstructure and Energy Dispersion Spectrum of Scoria

The structure and morphology of materials were observed by scanning electron microscopy. The results revealed uneven surfaces and abundant pore structures, with pore diameters ranging from 5 to 14 μ m. Moreover, the materials were found to contain a large number of well-developed microscopic pore structures that provided the optimum conditions for scoria to adsorb antibiotics. As shown in the SEM micrographs, the surface of scoria was relatively smooth before adsorption compared with that after adsorption, and there were few granular substances on the surface before adsorption. Moreover, some antibiotics collected on the surface and in the surface pores of scoria after adsorption, resulting in the surface becoming rough (Fig. 10).

The components and characteristics of scoria are major factors influencing its absorption effects. The main compounds of scoria were found to be SiO_2 , Al_2O_3 , Fe_2O_3 , CaO, and MgO (Table 4). Silicate, which has a tetrahedral structure, was the primary mineral component. It promoted chemical adsorption [33]. The antibiotic was organic, and it is well known that organic compounds interact effectively with scoria on the micro level.

As shown in Figs 11-14, the carbon content of scoria was obviously higher after absorption than the original. Moreover, the peak height of C (carbon) showed greater variation than that of the other elements. This occurred because the test compounds were sulfa antibiotics (Table 6), which mainly consist of carbon and hydrogen.



Fig. 9. SEM micrograph after adsorption.



Fig. 10. SEM micrograph after adsorption.



Fig. 11. EDX spectrum of scoria before adsorption.



Fig. 12. EDX spectrum of scoria after adsorption of ST.



Fig. 13. EDX spectrum of scoria after adsorption of SM2.



Fig. 14. EDX spectrum of scoria after adsorption of SMX.

Table 6.	Basic	properties	and o	characteristics	of	three	sulfa	antibiotics	[35].	

Antibiotics	Sulfathiazole (ST)	Sulfamethazine (SM2)	Sulfamethoxazole (SMX)	
Structural formula				
Molecular formula	$C_9H_9O_2N_3S_2$	$C_{12}H_{14}N_4O_2S$	$C_{10}H_{11}N_{3}O_{3}S$	
Molecular weight (g mol ⁻¹)	255.3	278.3	253.3	
Density (g cm ⁻³)	1.70	1.39	1.08	
Solubility (g L ⁻¹)	1.56	0.49	1.73	

As a result, the carbon content of scoria increased after absorption, which agreed with the change of carbon content in the EDX spectrum of scoria after adsorption. Overall, the increasing carbon content indicates that the adsorption of the three antibiotics by scoria was effective.

Conclusions

- 1. The results showed that scoria adsorbed the three investigated antibiotics, and that the content of Fe²⁺ and Mn²⁺ water hardness and alkalinity in water influenced the adsorption of these compounds. Uneven surfaces and the abundant pore structures of scoria were well developed, which provided good conditions for the adsorption of antibiotics. Overall, scoria was a suitable material for the purification of water containing ST, SM2, and SMX.
- 2. Ions affected the adsorption of ST, SM2, and SMX by scoria in low-temperature water. However, the effects of ions on their adsorption differed, with Fe^{2+} and Mg^{2+} promoting the adsorption of the three kinds of antibiotics by scoria, while Ca^{2+} promoted their adsorption under some, but not all conditions. Conversely, Fe^{2+} , Mn^{2+} , and CO_3^{2-} led to decreases in the adsorption of ST, SM2, and SMX of 16, 6, and 4%, respectively.
- 3. Kinetic data describing the adsorption were best described by the pseudo second-order model, while the equilibrium experiment data were described by the Freundlich model. Additionally, the rate-limiting step of the process was found to be the adsorption mechanism. The main mineral components of scoria were quartz, alkali feldspar, and plagioclase. Comprehensive research and the EDX spectra of scoria indicated that micro collisions occurred between these materials and antibiotics during the experiment, resulting in their removal from water.

Acknowledgements

We acknowledge financial support from the major science and technology project of rural drinking water safety (No. 2012BAJ25B10).

References

- SINGER R.S, FINCH R., WEGENER H.C, BYWATER R., WALTERS J., LIPSITCH M. Antibiotic resistance – the interplay between antibiotic use in animals and human beings. The Lancet Infect. Dis. 3 (1), 47, 2003.
- CABELLO F.C, Heavy use of prophylactic antibiotics in aquaculture: a growing problem for human and animal health and for the environment. Environ. Microbiol. 8 (7), 1137, 2006.
- 3. KOLPIN D.W, FURLONG E.T, MEYER M.T, THURMAN E.M, ZAUGG S.D, BARBER L.B, BUXTON H.T.

Pharmaceuticals, Hormones, and Other Organic Wastewater Contaminants in U.S. Streams, 1999-2000: A national reconnaissance. Environ. Sci. Technol. **36** (6) 1202, **2002**.

- KARTHIKEYAN K.G., MEYER M.T. Occurrence of antibiotics in wastewater treatment facilities in Wisconsin, USA, Sci. Total. Environ. 361 (1-3), 196, 2006.
- ZHANG D., LIN L., LUO Z. Occurrence of selected antibiotics in Jiulongjiang River in various seasons, South China. Environ. Monit. 13 (7), 1953, 2011.
- 6. SARMAH A.K., MEYER M.T., BOXALL A. A global perspective on the use, sales, exposure pathways, occurrence, fate and effects of veterinary antibiotics (VAs) in the environment .Chemosphere. **65** (5), 725, **2006**.
- SACHER F., LANG F., BRAUCH H., BLANKENHORN I. Pharmaceuticals in groundwater: analytical methods and results of a monitoring Program in Baden-Württemberg, Germany. Journal of Chromatography A. 938 (1-2), 199, 2001.
- SU Z. Study on Determination Method for 24 Antibiotics in Aquatic Environment Samples and Its Application. Xiamen, Xiamen University. 2008 [In China].
- BELLANTE D.M.G., BELLANTE L., CHIAVOLA A., APRILE L.D., SBAFFONI S. Pharmaceuticals in the environment .Regulatory Toxicology Pharmacology. 28 (3), 212, 1998.
- WEBB S.F. A data-based perspective on the environmental risk assessment of human pharmaceuticals II: Indirect human exposure, in: K. Kummerer (Ed.), Pharmaceuticals in the Environment, Springer-Verlag, Berlin, 221, 1999 [In Germany].
- MICHELE E., LINDSEY, MEYER M., THURMAN E. Analysis of trace levels of sulfonamide and tetracycline antibiotics in groundwater and surface water using solid-Phase extraction and liquid chromatography/mass spectrometry. Analytical Chemistry. **73** (19), 4640, **2001** [In U.S].
- GOKOGLU E., YILMAZ E. Fluorescence Interaction and Determination of Sulfathiazole with Trypsin. Journal of Fluorescence. 24 (5), 1439, 2014.
- MARTINELLO M., BAGGIO A., GALLINA A., MUTINELLI F. Distribution of Sulfathiazole in Honey, Beeswax, and Honeybees and the Persistence of Residues in Treated Hives. J. Agric. Food Chem. 61 (38), 9275, 2013.
- GAO Y., GAO N., DENG Y., GU J., ZHANG D. Factor affecting sonolytic degradation of sulfamethazine in water. Ultrasonics Sonochemistry. 20 (6), 1401, 2013.
- PENG F., YING G., LIU Y., SU H., HE L. Joint antibacterial activity of soil-adsorbed antibiotics trimethoprim and sulfamethazine. Science of The Total Environment. 506 (15), 58, 2015.
- SU T., DENG H., JONATHAN P., MICHAEL R. Biodegradation of sulfamethoxazole photo-transformation products in a water/sediment test. Chemosphere. 148, 518, 2016.
- GYURI S., KRISZTINA K., ANIKO B., TAMAS C., ERZSEBET T., LASZLO W. Enhancing the biological degradability of sulfamethoxazole by ionizing radiation treatment in aqueous solution. Radiation Physics and Chemistry. 124 (6), 179, 2016.
- AI-XIA Z., XIAO-SI S., SONG G., YU-LING Z., XUE-YU L., LAN-YING Z., YONG-LEI. Determination of Four Sulfa Antibiotics in Groundwater, Soil and Excreta Samples Using High Performance Liquid Chromatography. Chinese J. Anal Chem. 42 (3), 397, 2014.
- 19. GöBEL A., THOMSEN A., MCARDELL C.S., JOSS A., GIGER W., Occurrence and Sorption Behavior of

Sulfonamides, Macrolides, and Trimethoprim in Activated Sludge. Treatment. Environmental Science & Technology. **39** (11), 3981, **2005**.

- YU F., LI Y., HAN S., MA J.. Adsorptive removal of antibiotics from aqueous solution using carbon materials. Chemosphere. 153(6), 365, 2016.
- CHOI Y., KIM L., ZOH K. Removal characteristics and mechanism of antibiotics using constructed wetlands. Ecological Engineering. 91 (6), 85, 2016.
- AHMED M., ZHOU J., NGO H., GUO W. Adsorptive removal of antibiotics from water and wastewater: Progress and challenges. Science of The Total Environment. 532 (11), 112, 2015.
- ROOKLIDGE S.J., MINER J.R., KASSIM T.A., NELSON, P.O. Antimicrobial contaminant removal by multistage slow sand filtration. American Water Works Association. 97 (12), 92, 2005.
- KOSUTIC K., DOLAR D., ASPERGER D., KUNST B. Removal of antibiotics from a model wastewater by RO/NF membranes. Separation and Purification Technology. 53 (3), 244, 2007.
- Snyder S.A., WESTERHOFF P., YOON Y., SEDLAK D. L. Pharmaceuticals, personal care products, and endocrine disruptors in water: implications for the water industry. Environ Eng Sci. 20 (5), 449, 2003.
- SHANNAG M.J., CHARIF A., DGHAITHER S. Developing Structural Lightweight Concrete Using Volcanic Scoria Available in Saudi Arabia. Arab J Sci Eng. 39 (5), 3525, 2014.

- ZHANG S., LU Y., LIN X., SU X., ZHANG Y. Removal of fluoride from groundwater by adsorption onto La(III)-Al(III) loaded scoria adsorbent. Applied Surface Science. 303 (1), 1, 2014.
- ZHANG Y., DONG T., SU X., QIAN H., WANG J. Effect of high fluoride groundwater purification by lightweight aggregate scoria. Environmental Earth Sciences. 75 (1), 1, 2016.
- PERALTA V., CUESTA M.J., MATA I., SERRANO J.F., PEREZ N F., NATIVIDAD M.C. Serum iron in catatonic and non-catatonic psychotic patients. Biol Psychiatry. 45 (6), 788, 1999.
- ROSEBUSH P.I., MAZUREK M.F. Serum iron and neuroleptic malignant syndrome. Lancet. 338 (8760), 149, 1991.
- BROWN K., GLEN S., WHITE T. Low serum iron status and akathisia. Lancet. 1 (8544) 1234, 1987.
- ENTEZARI M.H., TAHMASBI M. Water softening by combination of ultrasound and ion exchange. Ultrasonics Sonochemistry. 16 (3), 356, 2009.
- BASF Pocket Book for the Leather Technologist, third ed, Germany, 57, 1995.
- ZHANG S., ZHANG Y., SU X., ZHANG Y. Purification of Petroleum Contaminated Groundwater by Permeable Reactive Barrier Using Scoria as Media. Journal of Jilin University. 42, 393, 2012.
- ZHOU A. Research on the Migration and Transformation Mechanism and remediation technique of sulfa antibiotics in phreatic water. Changchun, Jilin University. 2014 [In China].